

REGENERADORES *Regenerators*

RG-611-A

6 x GN 1/1.



5.650 W



140°C / 160°C



52 Kg.



400 / 230 V / 50-60 Hz



CARACTERÍSTICAS *features*

- | | |
|--|--|
| <ul style="list-style-type: none"> ● DIMENSIONES INTERNAS: (W)594x(D)386x(H)451 mm <i>cooking chamber dimension</i> | <ul style="list-style-type: none"> ● POTENCIA: 5.650 W <i>power</i> |
| <ul style="list-style-type: none"> ● DIMENSIONES EXTERNAS: (W)735x(D)710x(H)720 mm <i>external dimension</i> | <ul style="list-style-type: none"> ● TEMPERATURA MÁXIMA: 140° / 160° C <i>max temperature</i> |
| <ul style="list-style-type: none"> ● CONEXIÓN: Trifásica 3F+N+T / Monofásica 3p + n + e three phase / single phase | <ul style="list-style-type: none"> ● PESO: 52 Kg. <i>weight</i> |
| <ul style="list-style-type: none"> ● DISTANCIA ENTRE PARRILLAS: 65 mm. <i>distance between trays</i> | <ul style="list-style-type: none"> ● VOLTAJE: 400 / 230 V / 50-60 Hz. <i>Voltage</i> |

EQUIPAMIENTO *equipment*

- | | |
|--|---|
| <ul style="list-style-type: none"> ● Temporizador 0-60 min. <i>timer 0-60 min.</i> ● Termostato de seguridad <i>Safety thermostat</i> ● Micro de puerta <i>Door safety switch</i> | <ul style="list-style-type: none"> ● Alarma fin de ciclo <i>Cycle end alarm</i> ● Inversor de giro <i>Reversing gear</i> ● Cambio apertura puerta <i>Change opening door</i> |
|--|---|

PVP rrp **RG-611-A**