

SERIE M

M-604-PLUS

4 X 600 X 400 mm.



6.300 W




250° C



51 Kg.



400/230 V / 50-60 Hz



CARACTERÍSTICAS features

- DIMENSIONES INTERNAS: (W)680x(D)450x(H)360 mm
cooking chamber dimension
- DIMENSIONES EXTERNAS: (W)820x(D)800x(H)555 mm
external dimension
- DISTANCIA ENTRE PARRILLAS: 80 mm.
distance between trays
- CONEXIÓN: Trifasica 3F+N+T / Monofasica 3p + n + e
three phase / single phase
- DOTACIÓN: 4 Parrillas
including: 4 wire rack

- POTENCIA: 6.300 W
power
- TEMPERATURA MÁXIMA: 250° C
max temperature
- PESO: 51 Kg.
weight
- VOLTAJE: 400/230 V / 50-60 Hz
Voltage

EQUIPAMIENTO equipment

- Temporizador 0-60 min. + modo continuo
timer 0-60 min. + continuous function.
- Alarma fin de ciclo *Cycle end alarm*
- Micro de puerta *Door safety switch*

- Termostato de seguridad *Safety thermostat*
- Lámpara interior *Halogen chamber light*
- Inversor de giro *Reversing gear*
- Apertura reversible modelo (puerta lateral)
Reversible opening door (side door model) (RXL)

OPCIONES (PVP) options (rrp)

- HUMIFICADOR:
humidifier

PVP rrp M-604-PLUS

PVP rrp M-604-PLUS -L