



3.100 W



260° C



36 Kg.



230 V - 50 Hz



### CARACTERÍSTICAS features

- |   |  |
|---|--|
| <ul style="list-style-type: none"> <li>● DIMENSIONES INTERNAS: (W)500x(D)410x(H)345 mm<br/><i>cooking chamber dimension</i></li> <li>● DIMENSIONES EXTERNAS: (W)640x(D)720x(H)540 mm<br/><i>external dimension</i></li> <li>● DISTANCIA ENTRE PARRILLAS: 80 mm.<br/><i>distance between trays</i></li> <li>● CONEXIÓN: SCHUKO_MONOFASICO <i>single phase connection</i></li> <li>● DOTACIÓN: 4 Parrillas<br/><i>including: 4 wire rack</i></li> </ul> | <ul style="list-style-type: none"> <li>● POTENCIA: 3.100 W<br/><i>power</i></li> <li>● TEMPERATURA MÁXIMA: 260° C<br/><i>max temperature</i></li> <li>● PESO: 35 Kg.<br/><i>weight</i></li> <li>● VOLTAJE: 230 V / 50 Hz<br/><i>Voltage</i></li> </ul> |
|---|--|

### EQUIPAMIENTO equipment

- |  |  |
|--|--|
| <ul style="list-style-type: none"> <li>● Alarma fin de ciclo <i>Cycle end alarm</i></li> <li>● Micro de puerta <i>Door safety switch</i></li> <li>● Termostato de seguridad <i>Safety thermostat</i></li> <li>● Lámpara interior <i>Halogen chamber light</i></li> </ul> | <ul style="list-style-type: none"> <li>● Conexión agua ¾ <i>Water connection ¾</i></li> <li>● Humedad regulable 0-100% <i>Adjustable humidity 0% – 100 %</i></li> <li>● 99 Programas con tres fases cada uno <i>99 programs with three phases each</i></li> <li>● Precalentamiento automatico <i>Automatic pre-heating system</i></li> <li>● Apertura reversible modelo (puerta lateral)<br/><i>Reversible opening door (side door model) (RXL)</i></li> </ul> |
|--|--|

### OPCIONES (PVP) options (rrp)

- KIT GN 2/3:

PVP rrp ME-424

PVP rrp ME-424-L